



MADAME CURIESTRAAT 1, 2171 TW
SASSENHEIM, NETHERLANDS
INFO@MB-DUSTCONTROL.COM
WWW.SPRAYCANNON.COM
T. 0031(0)252-794010

SPRAYCANNON 40 SKID

WWW.SPRAYCANNON.COM

TECHNICAL SPECIFICATIONS

Usage	Outdoor
Distance (m)	25-40 (windstill cond.)
Surface (m ²)	4.400
Quantity of Nozzles	16
Water Usage (l/h)	1.000
Fan (kW)	3,0
Pump (kW)	1,5
Working Pressure (Bar)	40
Vertical Angle (°)	-15 to 60
Oscillation Angle (°)	0-320
Generator (kVA)	8 (Diesel)
Weight (kg)	739kg
Dimensions LxBxH (mm.)	1750x1250x1415

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



AVAILABLE OPTIONS

- ✓ Electrical Oscillation
- ✓ Electrical Elevation
- ✓ Fan Speed regulation
- ✓ Remote Control
- ✓ UV installation
- ✓ Wheel set
- ✓ Trailer

WE BEAT ODOUR AND DUST!