



MADAME CURIESTRAAT 1, 2171 TW
SASSENHEIM, NETHERLANDS
INFO@MB-DUSTCONTROL.COM
WWW.SPRAYCANNON.COM
T. 0031(0)252-794010

SPRAYCANNON 15

WWW.SPRAYCANNON.COM

TECHNICAL SPECIFICATIONS

Usage	Indoor/Outdoor
Distance (m)	10-20 (windstill cond.)
Surface (m ²)	40
Quantity of Nozzles	9
Water Usage (l/h)	1-200
Fan (kW)	0,28
Pump (kW)	No
Working Pressure (Bar)	-
Vertical Angle (°)	0-90
Oscillation Angle (°)	No
Electricity	110V/230V
Supply Connection	1"
Supply Pressure (Bar)	1-9
Dimensions LxBxH (mm.)	550x440x730
Weight (kg.)	18

APPLICATION AREAS

DEMOLITION - CONCRETE PRODUCTION PLANTS - RECYCLING SITES & PLANTS - ENVIRONMENTAL SITES; SOIL REMEDIATION - STEEL/SLAG HANDLING SITES & PLANTS - WOOD/ALUMINUM PROCESSING PLANTS - FIREFIGHTING - THE SPRAYCANNONS ARE ALSO USED FOR COOLING DOWN BULK MATERIALS, MACHINES AND PERSONS.



STANDARD EQUIPPED WITH

- ✓ Fan Speed regulation
- ✓ Water Flow regulation

WE BEAT ODOUR AND DUST!